



■ Clamping force TZ42-76





■ Technical Parameter

Product properties	TZ42-76	TZ42-76-NO	TZ42-76-NC	Unit
Single stroke	6	6	6	mm
Weight	0.5	0.75	0.75	kg
Max. clamp pistonce	90	90	90	mm
Fitting size	M5	M5	M5	
Girpping force: open/close	120*P/108*P	120*P	108*P	N
Max. locking force		340	340	N
Min. locking force		240	240	N
Workpiece weight	3	3	3	kg
Continuation max frequency	40	30	30	cpm
Repeat accuracy	±0.02	±0.02	±0.02	mm
Air pressure	3~7	4~7	4~7	bar
Ambient temperature	0~60	0-60	0~60	°C
IP grade		45		


P: Air Pressure [bar]


WWW.FOUK.TOP FOUK | 28

27 | FOUK* WWW.FOUK.TOP

TZ42-76 2-M3 Air feed-throughs 3x2-M4 ∓ 6 Bottom Port Dimension (B): Recommended connecting flange size $\phi 5.5 \pm 0.7$, seal ring $\phi 3.5*1$. 2-M5 Air feed-throughs /

TZ42-76-C20 Push plate






Accessory description:

TZ42 series opening up the pushing interface and offers different optional heights of 20.5mm and 30.5mm. Dust cover plate promoted 7.5mm. Pushing plate floats to provide thrust and the high quality hardened spring provides over 500,000 cycles of service life to ensure its functional reliability under prolonged impact.


TZ42-76-NO/NC Self-locking type




Accessory description:

TZ42 series optional open/close self-locking module can maintain the clamping status even in the case of low air pressure or loss of air supply, providing self-locking function and increasing the stability of clamping action at the same time.

TZ42-76-P Dust proof type







Accessory description:

Considering the diverse and complex working conditions of the gripper, the gripper is required to have better dust-proof performance. The TZ42 series is equipped with optional dust-proof unit, and the protection level is upgraded to IP55 to further enhance the performance of the gripper under complex working conditions.

TZ42-76-P-NO/NC Self-locking Dust proof type





Accessory description:

The TZ42 series offers a com bination of dust-proof module and self-locking module to meet more diverse application scenar ios and customer needs.

29 | FOUK* WWW.FOUK.TOP WWW.FOUK.TOP FOUK | 30