

FOUK-GS Rotary finger serial

GS40-180°

GS40

Static Bearing Torque



GS

40

- 180°

Serial No
GS Rotary Finger

Model

Rotation angle and direction

90°- L Left	180°- Rotation
90°-R Right	F Counter-bearings


Magnetic Proximity Sensor

D-M9NAL	Magnetic, NPN, 3core3m
D-M9PAL	Magnetic, PNP, 3core3m

*Each rotating unit requires two sensors to monitor two positions. See Sensor Appendix


Specification	GS40-180°	GS40-90° -L	GS40-90° -R	GS40-F	Unit
Rotation Angle	180	90	90		°
Rotation Direction		左	右		
End Position Adjustability	± 3	± 3	± 3		°
Torque	10	10	10		Nm
Weight	5	5	5	4	kg
Swiveling Time	0.4	0.4	0.4		s
Air Consumption	63	32	32		cm ³
Sensor Type	magnetic proximity sensor				

Buffer Specifications	M25 Hydraulic Buffer	Air Port Specification	G1/8
Repeated Accuracy/°	± 0.07	Ambient Temperature/°C	5~60
AirRange/bar	3~8	IP	54




GS40-90° -L Rotation Left

GS40-90° -R Rotation Right



GS40-F Counter-bearings

Note: Counter-bearings model is compatible with GS40-180° /90° .



GS40 Direct Air Connection

Note: No air fittings are allowed for this air port.

